



ARRESTER RATING CHART

System L-L Voltage kV		Arrester MCOV (kV)		
		Grounded Neutral Circuits (Wye)	Temporarily Undergrounded, Impedance Grounded or Undergrounded Circuits (Delta)	
Nominal	Maximum			(1)
2.40	2.52	2.55	2.55	2.55
4.16	4.37	2.55	5.1	5.1
4.8	5.04	5.1	5.1	5.1
6.9	7.25	5.1	7.65	7.65
8.32	8.74	5.1	7.65	8.4
12	12.6	7.65	10.2	12.7
12.47	13.1	7.65	12.7	12.7
13.2	13.9	8.4	12.7	12.7
13.8	14.5	8.4	12.7	15.3
20.78	21.8	12.7	19.5	22
22.86	24	15.3	19.5	22
23	24.2	15.3	19.5	22
24.94	26.2	15.3	22	24
34.5	36.2	22	29	36
46	48.3	29	39	48
69	72.5	42	57	70
115	121	70	98	115
138	145	84	115	131
161	169	98	140	152
230	242	140	209	220
345	362	209	---	---
400	420	245	---	---

(1) For Normal Duty. Line-to-ground fault up to 30 minutes.

(2) For Severe Duty. Line-to-ground fault up to 2,000 hours.

1-800-433-3128

components@sunbeltusa.com