



THREE PHASE PADMOUNTED TRANSFORMER (WITH OPTIONAL FUSING \*)  
 RADIAL FEED—LIVE/DEAD FRONT—150 KV BIL (HIGH VOLTAGE 35 KV AND BELOW)  
 \* BAYONET FUSING MAY NOT BE APPLICABLE TO SOME UNITS



ITEM	DESCRIPTION
1	COOLING PANELS
2	LIFTING LUGS
3	PROVISIONS FOR JACKING
4	HANDHOLE WITH COVER
5	CABINET
6	STEEL HI/LO BARRIER
7	1" NPT FILL/FILTER PRESS CONNECTION
8	PRESSURE RELIEF VALVE
9	LIQUID LEVEL GAUGE
10	LIQUID TEMP. GAUGE
11	LV BUSHINGS
12	HV BUSHINGS
13	DRAIN VALVE WITH SAMPLER
14	PROVISIONS FOR ARRESTERS
15	1/2"-13 GROUND PADS

NOTE: DIMENSIONS ARE FOR REFERENCE, NOT FOR CONSTRUCTION

KVA	A	B	C	D	E	F	G	H	J	K	WT	GAL
1000	79.00	72.25	79.81	40.00	46.00	59.56	39.50	29.75	20.00	74.25	9473	431
1500	79.00	70.50	78.31	40.00	46.00	61.56	37.75	29.75	20.00	74.50	12295	547
2000	86.00	74.50	86.56	48.00	55.00	66.31	38.50	33.00	24.00	78.00	15440	614
2500	86.00	75.50	90.31	47.00	55.00	66.56	36.50	33.00	24.00	79.50	16057	690